
## Food Waste Disposers





#### Dimensions



 $0^{-7}$ 

\* Distance from bottom of sink to center line of disposer outlet. Add 1/2" when stainless steel sinks are used.

NOTE: Plumb waste line to prevent standing water in disposer outlet to end of tailpipe. NOTE: Plumb waste line to prevent standing water in disposer motor housing.

### **Job Specifications**

### Submittal Sheet

This popular model offers the following features and benefits:

- 1/2 Horsepower Heavy Duty Motor (Quiet Dura-Drive<sup>®</sup> Induction Motor)
- We Come To You® 2-Year In-Home Limited Warranty
- Rugged Galvanized Steel Construction (For Disposer Durability)
- Space-Saving Compact Design
- Available with or without a factory installed power cord.

#### Sample Specification

Food Waste Disposer(s) shall be InSinkErator Badger® 5, continuous feed, with 1/2 H.P. motor, galvanized steel grinding elements with two stainless steel 360° swivel lugs. Self-service wrench.

Available with or without a factory installed power cord.

Warranty:

2-Year parts and in-home service.

\* The complete InSinkErator warranty is included in the Care & Use Booklet packed with each unit.

# Food waste disposers can provide an environmentally responsible alternative to transporting food waste to landfills. And they can help reduce greenhouse gas emissions. At capable wastewater treatment plants, food waste can be recycled to produce renewable energy. Additionally, capable wastewater treatment plants can process food waste into fertilizer. (Check the plant in your area.)





The Emerson logo is a trademark and service mark of Emerson Electric Co. The mounting collar configuration is a trademark of Emerson Electric Co.

InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

#### 1-800-558-5700 www.insinkerator.com

**Specifications** 

Continuous

Wall Switch

Single Phase

Intermittent

Permanently

Condor Grey

Manual Reset

Approx. 1 Gallon per Person Per Day

3-4 KWh per Year 1-1/2" Cushioned Slip Joint

Available with or without

Overload

11-1/2"

26 oz.

Yes

Lubricated Upper & Lower Bearings

13 lbs. 10 oz. (without cord) 13 lbs. 14 oz. (with cord)

1/2

120

60

1725

6.3

Type of Feed

Motor

HP

ΗZ

Volts

RPM

On/Off Control

Amp. (Avg. Load)

Shipping Weight (Approx.)

Time Rating

Lubrication

Unit Finish

Motor Protection

Average Water Usage

Dishwasher

Power Cord

Drain Connection

Average Electrical Usage

Drain Connection

Factory Installed

**Overall Height** 

Grind Chamber Capacity